

Oprava mostu v km 412,700
v žst. Praha-Bubny

v TÚ 0801 Praha Masarykovo nádraží st. 4 (m.) - Děčín hl. n. (včetně)

km 412,616 400 - 412,767 100

Souřadnice hlavních bodů

Číslo bodu	Popis bodu	Staničení	Souřadnice		Výška Z	Výška polygonu
			Y	X		
		[m]	[m]	[m]	[m]	[m]
1000	ZU	412616.400	741405.767952	1041076.358060	192.290	192.290
1001	ZZO	412620.597	741407.825235	1041072.699808	192.282	
1002	LN	412622.679	741408.845645	1041070.885320	192.278	192.279
1003	KZO	412624.761	741409.866055	1041069.070832	192.271	
1004	ZO	412642.042	741418.336789	1041054.008211	192.204	
1005	ZZO	412647.520	741421.039494	1041049.243090	192.182	
1006	LN	412650.000	741422.274459	1041047.092403	192.174	192.173
1007	KZO	412652.480	741423.516528	1041044.945811	192.169	
1008	SO	412660.437	741427.549330	1041038.086712	192.158	
1009	KO	412678.832	741437.149565	1041022.395933	192.132	
1010	ZO	412712.221	741454.923501	1040994.130476	192.085	
1011	ZZO	412713.841	741455.782016	1040992.756986	192.083	
1012	SO	412716.623	741457.239002	1040990.387541	192.077	
1013	KO/ZO	412721.024	741459.499344	1040986.611039	192.060	
1014	LN	412721.427	741459.703721	1040986.264137	192.058	192.072
1015	KZO	412729.012	741463.606212	1040979.759575	192.004	
1016	SO	412744.078	741471.647596	1040967.019678	191.869	
1017	ZZO	412746.575	741473.017113	1040964.932111	191.846	
1018	LN	412756.312	741478.457579	1040956.856332	191.782	191.759
1020	KZO	412766.050	741484.054280	1040948.888031	191.766	
1021	KO/KU	412767.132	741484.685795	1040948.009283	191.767	191.767

Oprava mostu v km 412,700
v žst. Praha-Bubny

v TÚ 0801 Praha Masarykovo nádraží st. 4 (m.) - Děčín hl. n. (včetně)

km 412,616 400 - 412,767 100

Psaný podélný profil

Číslo bodu	Popis bodu	Staničení	Vzdál. mezi body	Posun	Výška zam. Bodů	Niveleta	Zdvih	Lomy sklonu	Z	R _v	t _z	y _v
		[m]	[m]	[mm]	[m]	[m]	[mm]		[m]	[m]	[m]	[m]
1000	ZU	412616.400				192.290		-1.802 ‰				
292		412616.400		0	192.286	192.291	+ 5					
1001	ZZO	412620.597				192.282		-1.802 ‰				
1002	LN	412622.679				192.278		=====	192.279	2000.000	2.082	-0.001
1003	KZO	412624.761				192.271		-3.883 ‰				
880		412641.376		7 P	192.201	192.206	+ 5					
1004	ZO	412642.042				192.204						
1005	ZZO	412647.520				192.182		-3.883 ‰				
1006	LN	412650.000				192.174		=====	192.173	2000.000	2.480	0.002
1007	KZO	412652.480				192.169		-1.403 ‰				
1008	SO	412660.437				192.158						
1009	KO	412678.832				192.132						
905		412693.082		0	192.018	192.112	+ 94					
907		412711.279		0	191.988	192.087	+ 99					
1010	ZO	412712.221				192.085						
1011	ZZO	412713.841				192.083		-1.403 ‰				
1012	SO	412716.623				192.077						
1013	KO/ZO	412721.024				192.060						
1014	LN	412721.427				192.058		=====	192.072	2000.000	7.586	-0.014
1015	KZO	412729.012				192.004		-8.989 ‰				
1016	SO	412744.078				191.869						
1017	ZZO	412746.575				191.846		-8.989 ‰				
1018	LN	412756.312				191.782		=====	191.759	2000.000	9.738	0.024
1020	KZO	412766.050				191.766		0.749 ‰				
1021	KO/KU	412767.132				191.767		0.749 ‰				

Oprava mostu v km 412,700
v žst. Praha-Bubny

v TÚ 0801 Praha Masarykovo nádraží st. 4 (m.) - Děčín hl. n. (včetně)

km 412,616 400 - 412,767 100

Směrové parametry osy

Délka oblouku (jednoduchého - složeného oblouku)			L_i	číslo	R	L_i	orientace	α	V	I	D	a_q	n	L_k	L_d
od km	do km		(přímá)	oblouku		(kružnicový oblouk)									
[m]	[m]	[m]	[m]		[m]	[m]		[grad]	[km/h]	[mm]	[mm]	[m*s ⁻²]		[m]	[m]
			25.642												
412642.042	412678.832	36.790		1	750	36.790		3.122860	40	26	0	0.164609			
			33.389												
412712.221	412721.024	8.803		2.1	300	8.803		1.867970	40	63	0	0.411523			
			slož.												
412721.024	412767.132	46.108		2.2	500	46.108		5.870701	40	38	0	0.246914			

Oprava mostu v km 412,700

v žst. Praha-Bubny

v TÚ 0801 Praha Masarykovo nádraží st. 4 (m.) - Děčín hl. n. (včetně)

km 412,616 400 - 412,767 100

Výškové parametry osy

Číslo bodu	Staničení	Z	R_v	s	s	t_z	y_v
	[m]	[m]	[m]	[‰]	[‰]	[m]	[m]
1000	412616.400	192.290			-1.80		
1002	412622.679	192.279	2000	-1.80	-3.88	2.08	-0.001
1006	412650.000	192.173	2000	-3.88	-1.40	2.48	0.002
1014	412721.427	192.072	2000	-1.40	-8.99	7.59	-0.014
1018	412756.312	191.759	2000	-8.99	0.75	9.74	0.024
1021	412767.132	191.767		0.75			