

## General information

Item no.	51351
Device key	0131-A-20,0-FF-PV-KM26-230/50-16* JH54
Item description	2/2-way-solenoid valve f.aggress. medium
Program	S
Net weight	1.03 KG
CE	CEXX
Shipping time	7 Days
Statistical good	84818079

## Explanation of device key

Typ (TYP_0009)	0131
Circuit function (WW)	A - 2/2-ways; normally closed
Orifice size (DN)	20,0 - 20mm (3/4")
Seal material (DWST)	FF - FKM
Material (WKST)	PV - PVC
Port connection (LTA)	KM26 - solvent cement socket, diam. 25mm
Voltage (SP)	230 - 230 volts
Frequency (FR)	50 - 50 Hz
Power consumption (LEIS)	16 - 16 watt
Variable code 1 (VAR1)	JH54 - Cable plug type 2518 (00314802), without wiring 3 poles, 0-250 V AC/DC

## Technical data

Ambient temperature (max)	50
Ambient temperature (min)	-10
Closing time (msec) (max)	60
Closing time (msec) (min)	40
Duty cycle (%)	100
KV value (M*3/H)	6,000
Medium temperature (degree C) (max)	50
Medium temperature (degree C) (min)	-10
Opening time (msec) (max)	20
Opening time (msec) (min)	10
Pressure (bar) (max)	0,5
Pressure (bar) (min)	0
QNN value (L/MIN)	6400