

# TECHNOLOGICKÝ DOMEK TD

Technologický domek BTS je součástí technologické a sdělovací části dokumentace - část 2.

Elektro rozvadeč RE zasazen ve fasádě TD

Klimatizace

Technical drawing of a house cross-section showing structural details and dimensions. The drawing includes the following elements:

- Dimensions:**
  - Overall height: 1140
  - Overall width: 3480
  - Internal width: 2340
  - Internal height: 2160
  - Foundation height: 120
  - Basement height: 900
- Structural Details:**
  - KOTVENÍ PROFILY JTA:** Anchoring profiles for the roof structure.
  - Trusla PVC 120 x 120:** PVC trusses.
  - OSB krovová:** OSB roof sheathing.
  - IDE-A-M1250x68:** A specific structural component or fastener.
- Other Labels:**
  - 1140
  - 3480
  - 2340
  - 2160
  - 120
  - 900

Technical drawing of a room layout showing dimensions and equipment placement. The drawing includes a floor plan with a dashed outer boundary and a solid inner boundary. The room is labeled "ELEKROSTATICKÁ VODIVÁ PODLAHA - PVC". Equipment shown includes a "ROZVÁDĚČ" (circuit breaker) and a "MALÁ KLIMATIZACE" (small air conditioner). Dimensions are provided in millimeters (mm) and meters (m). The drawing also shows a section line A-A and a section line B-B.

Dimensions (mm):

- Overall width: 3100
- Overall height: 2500
- Room width: 2780
- Room height: 2180
- Distance from left wall to equipment: 100
- Distance from right wall to equipment: 100
- Distance from bottom wall to equipment: 100
- Distance from top wall to equipment: 100
- Distance between equipment: 200
- Distance between equipment: 425
- Distance between equipment: 2102
- Distance between equipment: 102
- Distance between equipment: 102
- Distance between equipment: 10

Equipment:

- ROZVÁDĚČ
- MALÁ KLIMATIZACE

Section lines:

- A-A
- B-B

- zařízení EZS proti vniknutí nepovolaných osob
- zařízení protipožární ochrany
- klimatizační zařízení s temperováním
- základní elektroinstalace
- vnější NN rozvaděč s výbavou
- vnitřní NN rozvaděč s výbavou a dohledem

- zateplená betonová buňka
- zastavěná plocha: 7,750 m<sup>2</sup>
- obestavěný prostor: 27,140 m<sup>3</sup> (sedlová střecha)
- hmotnost: 11,720 t (sedlová střecha)

- beton C35/45 - XC4, XF1
- výztuž - svařované sítě, ocel 10 505
- krytí výztuže interier 20mm
- krytí výztuže exterior 30mm

DOKUMENT LZE UŽÍVAT POUZE VE SMYSLU PŘÍSLUŠNÉ SMLOUVY O DÍLO. ŽÁDNÁ JEHO ČÁST NEMŮŽE BÝT DLE ZÁKONA č.121/2000 Sb. KOPÍROVÁNA NEBO JINÝM ZPŮSOBEM ROZŠÍŘOVÁNA. BEZ SOUHLASU SUDOP PRAHA a.s.